

MANUFACTURER'S WARRANTY

Service life, of the water filter (excluding replacement filter cartridges) is 5 years* from manufacturing date**. The water filter shall be replaced upon expiration of the service life.***

Service life of the replacement filter cartridges of various filter types: Pro 3 — Pro 7 — 10 000 liters but not more than 1 year****, Pro 1 — Pro HF — 8000 liters but not more than 1 year****.

Service life of the cartridges is calculated starting from the day they are purchased at the retail.

The purchase date of the water filter (with the replacement filter cartridges) is the date of the retailer's stamp in this product certificate or date of the sales receipt. If the purchase date is not available, the service life is calculated from the replacement filter cartridges manufacturing date.

Store at temperatures from +5 °C to +40 °C in a closed packaging.

* Regardless of the operation starting date.

** Manufacturing date is the date in the format DD MM YYYY shown by the manufacturer on the label placed on the back of the housing.

*** Using the water filter beyond its service life term may result in harm to the health or property of the consumer or third persons and shall be avoided.

**** The resource of the replacement cartridge is set for water filtration that meets the current sanitary standards. The service life of a replacement cartridge may vary depending on the quality of the water (hardness, amount of impurities, etc.).

AQUAPHOR®

Certified title:

Water purifier Aquaphor model Duo Pro;
Water purifier Aquaphor model Duo HF Pro.

The manufacturer reserves the right to make improvements in the water purifier design without depicting them in the product certificate.

The model number, manufacturing and quality control date are indicated on the special sticker with the product serial number.

1 Aquaphor Duo Pro

2 Aquaphor Duo HF Pro

Warranty period of the water filter operation (excluding the replacement filter cartridges) is 2 years from the purchase date. The manufacturer shall bear no warranty if this product certificate containing dates of manufacturing and/or sale is lost and there are no other ways to determine the period of the product operation.

The manufacturer shall bear no responsibility in any of the following cases:

- the customer does not follow installation instructions described herein;
- replacement filter cartridges are not replaced in due course after their service life has expired;
- the water filter is used beyond the limits set by the technical specifications (in the Manual).

Please contact the retailer or the manufacturer in case of any claims to operation of the water filter. No claims are accepted if the water filter has any visible external defects.

Manufacturer: Aquaphor International OÜ, L. Tolstoi 2A, Sillamäe, Estonia, 40231, sales@aquaphor.com.
www.aquaphor.com

Date of purchase / Retailer's stamp:

AQUAPHOR®

water filters

DUO PRO, DUO HF PRO

Manual

The Aquaphor DUO Pro is an advanced two-stage water filter designed for efficient drinking water purification. Its replacement filter cartridge utilizes cutting-edge carbon block technology, incorporating a filter matrix made of coconut-based granulated activated carbon (GAC) and AQUALEN™ ion-exchange fiber.

The water filter is specifically designed to treat chlorine, heavy metals, and organic impurities, ensuring the removal of harmful contaminants for cleaner and safer drinking water.

The Aquaphor DUO HF PRO filter contains a hollow-fiber membrane that removes particles larger than 0.1 microns, such as microorganisms and bacteria*.

Easy cartridge replacement

Instant replacement of cartridges.
Clean and safe maintenance.

Performance data:

Residual active chlorine	100%
Benzene	95%
Phenol	98%
Pesticides	97%
Heavy metals, (lead, cadmium)	95%

Technical characteristics

Model	Aquaphor Duo Pro	Aquaphor Duo HF Pro
Recommended use	Filtering drinking water	Filtering and conditioning drinking water using hollow fiber membrane, removal of micro-particles smaller than 0.1 microns
Replacement cartridge	Pro 3, Pro 7	Pro 1, Pro HF
Overall dimensions, no more than	187 × 106 × 342 mm	187 × 106 × 342 mm
Maximum working water pressure	0.63 MPa (6.3 bar / 91 psi)	0.63 MPa (6.3 bar / 91 psi)
Water temperature	+5...+38 °C	+5...+38 °C
Resource replacement cartridge*	10 000 liters, but not more than 1 year	8 000 liters, but not more than 1 year
Recommended filtration rate (performance)	1.5 l/min	1.5 l/min
Weight, not more	2 kg	2 kg

DELIVERY SET

Housing (1)	1 pc.	Connection tube (5, 6)	2 pcs.
Replacement filter cartridges (2)	2 pcs.	Clean water tap (8)	1 set
Connection unit (3)	1 pc.	Operation manual	1 pc.
O-ring (4)	1 pc.	Packaging	1 pc.

* Tested on Escherichia coli 1257, Enterobacter cloacae, Pseudomonas aeruginosa, Lamblia intestinalis.

Fig. 3